

FIDES DAYLIGHTING INTEGRATION BUILDING MANAGEMENT

Disruptive Innovation

Standby zero with advanced interaction dimming for building managements system
Tangible benefits for Reliability, maintain free, wire free, easy to access by web

Jul.25.2016

NS Semicon Co.,Ltd.

SPECIAL CONSIDERATIONS

Standby power, also called **vampire power**, **vampire draw**, **phantom load**, or **leaking electricity** ("phantom load" and "**leaking electricity**" are defined technical terms with other meanings, adopted for this different purpose), refers to the **electric power** consumed by electronic and electrical appliances while they are switched off (but are designed to draw some power) or in a **standby mode**. This only occurs because some devices claimed to be "switched off" on the electronic interface, but are in a different state from switching off from the plug, or disconnecting from the plug, which can solve the problem of standby power completely. In fact, switching off at the plug is effective enough, there is no need to disconnect all devices from the plug. Some such devices offer **remote controls** and **digital clock** features to the user, while other devices, such as **power adapters** for disconnected electronic devices, consume power without offering any features (sometimes called **no-load power**). All of the above examples, such as the remote control, digital clock functions and, in the case of adapters, no-load power, are switched off just by switching off at the plug. However, for some devices with built-in internal battery, such as the phone, the standby functions can be stopped by removing the battery instead. In the past standby power was largely a non-issue for users, electricity providers, manufacturers, and government regulators. In the first decade of the twenty-first century awareness of the issue grew and it became an important consideration for all parties. Up to the middle of the decade, standby power was often several watts or even tens of watts per appliance. By 2010 regulations were in place in most developed countries restricting standby power of devices sold to one watt (and half that from 2013).

The **One Watt Initiative** was launched by the **IEA** in 1999 to ensure through international cooperation that by 2010 all new appliances sold in the world only use one watt in standby mode. This would reduce CO₂ emissions by 50 million tons in the OECD countries alone by 2010.

In July 2001 **U.S.** President **George W. Bush** signed an **Executive Order** directing federal agencies to "purchase products that use no more than one watt in their standby power consuming mode".^[12]

In July 2007 California's 2005 appliance standards came into effect, limiting external power supply standby power to 0.5 watts.^[13]

On 6 January 2010 the **European Commission** (EC) Regulation No 1275/2008 came into force. The regulations mandate that from 6 January 2010 "off mode" and standby power for electrical and electronic household and office equipment shall not exceed 1W, "standby plus" power (providing information or status display in addition to possible reactivation function) shall not exceed 2W. Equipment must where appropriate provide off mode and/or standby mode when the equipment is connected to the mains power source. These figures were halved on 6 January 2013.^[14]

MORE...

Now a day, realization of building management needs to daylight energy reduce and the some of sensing by low costs network system with substitution mechanical power switch for standby zero supports.

FIDES-Dimmer are only one of solution of efficiency by full of requirements building managements system. Such as mechanical switches substitution to epoch-making novel standby zero circuits theory with constant voltage drive dimming technology employed.

This technology can provide ideally makes very good cost effect an flicker free dimming with no data wire and AC switch for LED luminaire.

Operational Benefits


When a general lighting system try to dimming by ambient sensor. So, it could not provide dimming pleasant environment. This is approached in different ways. The daylight dimming can interactively reaction at any vicinity lighting environments to individually.

In addition to standby zero efficiency benefits are killed all data lines and switches to makes a saving install fees. With the just plugging AC line installations makes easy to old building transformation to energy efficiency Building Automation System building.

ARRA Section 1605 establishes requirements for federal government projects funded with stimulus monies: "None of the funds appropriated or otherwise made available by [the ARRA] may be used for a project for the construction, alteration, maintenance, or repair of a public building or public work unless all of the iron, steel, and manufactured goods used in the project are produced in the United States." Iron and steel used as components or subcomponents of other manufactured construction materials do not need to be produced in the United States. There is no requirement that components and subcomponents be U.S.-origin provided the manufactured construction material is "produced in the United States." (FAR 25.001(c)(4)) Section 1605 does not contain a domestic cost requirement. However, the government has not defined "produced" for purposes of the ARRA Buy American provision. Many commentators have adopted the "substantial transformation" test to determine whether a manufactured article is "produced" in the United States for purposes of Section 1605. Section 1605 contains a requirement that the Buy American provision be applied in a manner consistent with U.S. obligations under international agreements. As a result, national treatment is extended to products from countries with which the United States has entered a free trade agreement (e.g., Canada, Mexico, Bahrain, Chile, etc.) and to products from countries that have signed the WTO Government Procurement Agreement. National treatment is also extended to least developed countries (LDCs) (e.g., Bhutan, Mali, Zambia, etc.) but not to Caribbean basin countries (e.g., Belize, Haiti, Bahamas, etc.)

Share of LED lighting market


Market Share by Region, 2010



- Global LED Lighting market to reach \$16.5B in 2012, 11.3% share of total lighting
- 60% Comm, 25% Resdl, 15% Indl/Instl
- Key luminaire drivers: traffic lights, roadways, parking lots, and other outdoors

LED share of lighting market to exceed 25% by 2014

LED Lighting Market Value, 2009–2014 (US\$B)



The first LED lamps were introduced in the late 1990s. Since then, the unit costs have been steadily declining by double-digit percentages, making LED lighting technology viable for commercial, industrial and outdoor lighting applications. In addition, large strides have been made in improving the efficiency, lumen output and performance of LED lights. The global LED lighting market is estimated to be \$16B in 2012 and expected to reach nearly \$40B by 2014 (Figure 1). The US market CAGR for commercial and outdoor LED lighting alone is expected to grow 26-30% through 2016.

FIDES BUILDING MANAGEMENT SYSTEM



에너지 관리
Energy Administration



빌딩 설비 통합
Building Equipment
Integration



Zone 제어
Zone Control



편리한 사용자 인터페이스
User Friendly Interface



원격 제어 및 알람, SMS
Remote Control and
Alarm, SMS



오픈 프로토콜 지원
(BACnet, LonWorks, Modbus, OPC)
Open Protocol Support


Why Lighting is an Energy Issue

Lighting in all segments (residential, commercial, industrial, and outdoor) consumes almost 25% of the energy in the built environment, internationally. ¹

This energy is expended both in the electricity necessary to illuminate a given lightbulb, but also in cooling costs needed to counteract the heat produced by lighting fixtures. In fact, the heat produced by lighting alone contributes to 42% of the cooling load in U.S. buildings.²

The energy used by lighting amounts to 1.2 Terawatts (equivalent to 1,200 Gigawatts or 1,200,000 Megawatts), 112 full-sized power plants, and 1.9 billion tons of annual carbon emissions.³

If LEDs made up 45% of the world's lighting supply by 2020, we would forgo 5 trillion kWh of electricity, 559 full-sized power plants, and 8.4 billion tons of carbon emissions.⁴



¹ <http://www.undp.org.cn/projects/00062179.pdf>

² U.S. Department of Energy Buildings Energy Data Book, Sept. 2008

³ Based on United States Energy Information Administration estimates.

⁴ Ibid.

Power Consumption of BMS :

Standby zero, Daylight dimming



0.007%




Figure 1: Bullitt Center - Energy Use



American Reconstruction and Reinvestment Act of 2009



FIDES : STANDBY Energy Saving

STANDBY POWER MEASUREMENT RESULTS

12W LOAD	120V	220V
STANDBY	0.027W	0.035W
ON(LOAD)	12W	12W
200W LOAD	120V	220V
STANDBY	0.027W	0.035W
ON(LOAD)	200W	200W

Any load power participate are same for stand by power keep in under the 0.035W, during the first initializing plugged to AC line for few seconds to a few watts to charging for super capacitor. After it's only allowed leakage currents in traic switching driver circuits.

Power Consumption*1 - When the power is off: Any load equipment approximately 100V at 0.027 W *1*2*3 / At 220V approx 0.035 W *1*2

*1: Power consumption not varies. depending on the input voltage environment.

*2: Measured according to IEC 62301 Edition 2.0.

*3: Even when the machine is turned off, it will automatically turn itself on periodically for re charging maintenance, and then turn itself off.

Example of standby power consumption : 1W/h standby power SMPS X 1K pcs in building = 1KW/h
(Standby at 14h/day for year \approx 0.5MW/years

Same condition at Fides standby power consumption = 178W/years (0.5MW electric energy save!)

* IEC 62301 in large appliances manufacturers target <50 mW or '0.0W consumption'

FIDES DIMMER Vs ORDINARY DIMMER

	DALI	RF WIRELESS	FIDES
COSTS	✘	▲	😊
INSTALLATION	✘	✘	😊
STANDBY ZERO	✘	✘	😊
ADVANCED INTERACTION DIMMING	✘	▲	😊
CONNECTIVITY	✘	😊	😊
POWER CONSUMPTION	✘	✘	😊
AC POWER MEASUREMENT	✘	😊	😊
SMART GRID	✘	😊	😊
MULTI-SENSOR	✘	😊	😊
WEB CONTROL	▲	😊	😊



VERY GOOD



NOT GOOD



BAD


FIDES MERIT IS REAL INTERNET OF THINGS

FIDES BMS; disruption to ordinary BMS technologies chain.

	Ordinary BMS system	FIDES BMS system
IEC62031 Standby Zero	Not supports	Patent Technology
Individual dimmer	High Price	Good Price(Patent Pending)
Wire	Complicate	Just Plug AC Line
Temp, Humidity, Ambient	Option	Integrated
AC Power Line measure	Option	Integrated
Luminaire connection Limit	Limit	Unlimited
Fire alarm, Occupy Sensor	Option	Option(Just Plug in AP)
Management Software	Option	Default

* For more information refer to FIDES_ADSZ data sheet manual.

TYPICAL BMS ARCHITECTURE



Too much complicate!

FIDES-BMS ARCHITECTURE SUCCINCT GRID NETWORKS




Sustainable buildings





FIDES : Energy Saving

Daylight Individual Interaction Dimming




Daylight dimming




A daylight harvesting system decreases electric light contribution as the daylight contribution increases. Courtesy of Leviton.

Building management winner!



All in One Supports :

- IEC62301 Standby zero (Patent 0.035W/h)
- IEC62053-21 AC Power measurement
- Temp/Humidity/Ambient sense
- Full flicker free individual dimming
- Wire Free IrDA/2.4Ghz Smart Grid Network
- 10 years Limited Warranty







Typical daylight system

Not support :


- IEC62301 Standby zero not support
- IEC62053-21 AC Power measurement
- Temp/Humidity sense
- Full flicker free individual dimming
- No 10year warranty

Typical daylight harvesting control system.




Courtesy of Lawrence Berkeley National Laboratory.

DALI dimming wire connection




DALI BUS WIRE





Picture 3: Large DALI system with DALI routers

Too much complicate and expensive with no efficiency energy saving architecture system




Picture 2: Standalone DALI system

KNX BMS SOLUTION ARCHITECTURE




Connections




Wall box dimmers allow reduction of energy spent for lighting. Instead of having light only ON or OFF, light level can be adjusted to needed level. Dimming your light level just 25%, saves 20% in energy.

FIDES dimming wire connection




FIDES LUMINAIRE

More information refer to FIDES-ADSZ datasheet




American Reconstruction and Reinvestment Act of 2009

FIDES-BMS WIRE SYSTEM ONLY ONE AC LINE



FIDES LIGHTING BMS SYSTEM CONNECTS ALL JUST ONE AC WIRE



No Switch!, No Sensor cable!, No Controller!, No Gateway!

ONLY AC LINE WIRING!!!


As same for One Room to Whole Building

FIDES-AP BM PLACEMENTS

◆ DJ03A: place to each rooms

Functions :


- AC shutdown Switching
- Individual dimming
- Room Temperature
- Room Humidity
- Room Ambient
- Room Electric power consumption measurement
- Wireless network




Virtual Remote



DJ-03A WIRING



PRODUCTS



FIDES SMPS : AC-DC SMPS for IEC62301 Standby Zero, Dimming

DJ-01 : IrDA, Luminance sensor (Pair with FIDES SMPS)

DJ-02 : Remote controller

DJ-03 : Access Point 2.4Ghz and IrDA with IEC62036 Class II AC Power smart meter, Temp, Humidity, ambient sensor (AC85~275V 50/60Hz), Remote Shutdown SW(DJ-03A) (*1BMS OPTION*), *Direct WEB Server(DJ-03B)*

DJ-04 : USB Access Point Main Controller (*BMS OPTION*)

DJ-05 : FIDES-BMS Software (*BMS OPTION*)

* *1BMS* are supports multi rooms and environments measure

FIDES-BMS

DJ05 BMS SYSTEM
MANAGEMENT SOFTWARE

Initial screen

FIDES-BMS

AP 1



BMS POWER SWITCH

Screen of the selected AP

AC Power

3045W/h

Ambient

650lx

Temperature

23 °C

Humidity


55%



AC line live display



AP ON/OFF SW




Individual luminaire control (only numbers, such as watering)



ON/OFF



DIM HALT




DIMMING (45%)

LUX 570lx

COOPER LIGHTING

Dimming w/ BMS



RCQK-OS3E-OS1-SS1-W1-D1-B-W



The Room Controller includes three relays and up to three 0-10 VDC dimming outputs to control compatible dimmable ballasts. The switching relays and 0-10 VDC outputs are controlled separately allowing flexibility in wiring and control. The Room Controller is shipped preconfigured to work out of the box when connected to RC devices allowing quick and easy daylighting controls, occupancy/vacancy sensing and manual switching. Eliminate wiring errors and reduce installation time with Click & Go technology. Benefit from advanced features like UL 924, BMS integration, Egress and Demand Response while meeting energy codes. Single package QuickKit makes the Room Controller simple to specify, install and use.



Daylight Sensor



Occupancy Sensors



Switchpack



Wallstations




<http://cooperroomcontroller.sumoc.com/index.cfm?action=main.roomdetails&roomid=47c9b9c23e0e66c6013e1d91c11101f9&categoryid=6FA07EE6AF983C4384E7C6E064D5B716>



COOPER LIGHTING

Room Controller QuickKit RCQK-OS3E-OS1-SS1-W1-D1-P-W



Product Legend

-  **QTY1: RC3DE**
3 RELAY + 3 DIMMER + 1 EMERGENCY RELAY
-  **QTY1: RC-3TLB-OS1-W**
HALF LIGHTS, FULL LIGHTS, ALL OFF
-  **QTY:1 RC-SS1-W**
WHITE SLIDER
-  **QTY1: DSRC-FMOIR**
DAYLIGHT SENSOR
-  **QTY1: OAWC-DT-120W**
WALL CORNER VACANCY SENSOR
-  **QTY1: OCC-RJ45**
OCCUPANCY SENSOR RJ45 CONNECTOR
-  **QTY1: SPRC-R-20-120**
RECEPTACLE CONTROL
-  **QTY2: GGRJ45-10-G**
QUICKCONNECT CABLE 10'
-  **QTY3: GGRJ45-25-G**
QUICKCONNECT CABLE 25'
-  **SINGLE BOX PACKAGING WITH WIRING DETAIL AND INSTALLATION**
-  **RECESSED FIXTURE**
- FOR GUARANTEED COMPATIBILITY REFER TO PREFERRED COOPER LIGHTING FIXTURE INFORMATION BELOW.**

<http://cooperroomcontroller.sumoc.com/index.cfm?action=main.roomdetails&roomid=47c9b9c23f86a4bd01426d30addb2bc4&categoryid=6FA07EE6AF983C4384E7C6E064D5B716>




COOPER LIGHTING

ROOM CONTROLLER SAMPLE ROOM LAYOUT (30' x 30')

Room Controller QuickKit

RCQK-CR3-ES1-TS6-C1-DH-B-W



Product Legend



QTY1: RC3D
3 RELAY + 3 DIMMER



QTY1: RC-2TLB-ES1-W
(ENTRY, ALL OFF)



QTY1: RC-6TSB-TS6-W
(ENTRY, GENERAL, WHITEBOARD, RAISE, LOWER, ALL OFF)



QTY1: DSRC-FMOIR
DAYLIGHT SENSOR



QTY1: OAC-DT-2000
CEILING MOUNT VACANCY SENSOR 2000 SQ. FT.



QTY2: OCC-RJ45
OCCUPANCY SENSOR RJ45 CONNECTOR
BMS OUTPUT DEVICE



QTY1: HHPRG-RC
HANDHELD DAYLIGHT PROGRAMMER



QTY1: GGRJ45-10-G
QUICKCONNECT CABLE 10'



QTY3: GGRJ45-25-G
QUICKCONNECT CABLE 25'



QTY1: GGRJ45-50-G
QUICKCONNECT CABLE 50'

**SINGLE BOX PACKAGING WITH WIRING DETAIL
AND INSTALLATION**



RECESSED FIXTURE

**FOR GUARANTEED COMPATIBILITY REFER TO PREFERRED COOPER
LIGHTING FIXTURE INFORMATION BELOW.**